

DC12-120(12V120Ah)



Specification



DC (Deep Cycle) series batteries provide superior high integrity and reliability. It is specially designed for frequent cyclic charge and discharging. By using strong grids, thick plate and specially active material are designed for repeated deep-discharge applications. The DC series batteries offer 30% more cyclic life than the standby series. It is suitable for solar and wind renewable energy storage, mobility and medical equipment and cable TV etc.



ISO 9001



ISO 14001



OHSAS 18001




MH 28539



Cells Per Unit	6
Voltage Per Unit	12
Capacity	120Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 33.5 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 4.5 mΩ
Terminal	F5(M8)/F12(M8)
Max. Discharge Current	1200A (5 sec)
Design Life	12 years (floating charge)
Max. Charging Current	36.0 A
Reference Capacity	C3 91.7AH C5 103.4AH C10 114.3AH C20 120.0AH
Float Charging Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

Dimensions



Length	407±2mm (16.0 inches)
Width	177±2mm (6.97 inches)
Height	225±2mm (8.86 inches)
Total Height	225±2mm (8.86 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A(25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	276.8	217.7	130.7	72.88	43.40	33.81	26.52	22.56	14.47	12.00	6.219
1.65V	255.0	203.6	123.8	70.40	41.95	32.77	25.73	21.85	14.36	11.89	6.186
1.70V	236.3	191.5	117.4	68.14	40.83	31.38	24.93	21.26	14.13	11.66	6.108
1.75V	216.8	179.3	112.7	66.00	39.26	30.58	24.25	20.67	13.90	11.54	6.000
1.80V	197.3	164.2	108.6	63.07	37.92	30.00	23.69	20.40	13.67	11.43	5.942
1.85V	154.4	135.9	92.07	56.30	34.68	27.92	22.21	18.78	12.87	10.74	5.887

Constant Power Discharge Characteristics : WPC(25°C)


F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	471.3	379.8	237.5	136.8	82.06	64.20	51.11	42.70	28.20	23.53	12.42
1.65V	453.9	369.3	231.9	134.5	79.85	62.60	49.87	41.55	27.97	23.31	12.31
1.70V	423.6	349.5	220.7	130.5	77.85	60.20	48.28	40.51	27.63	22.85	12.19
1.75V	394.2	329.9	213.0	126.9	75.09	58.71	47.15	39.58	27.18	22.63	11.97
1.80V	363.2	305.0	206.1	121.7	73.38	58.38	46.24	39.05	26.73	22.40	11.86
1.85V	288.1	256.2	176.8	109.3	67.57	54.46	43.52	36.12	25.27	21.16	11.75

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.
The battery must be fully charged before the capacity test. The C₂₀ should reach 95% after the first cycle and 100% after the third cycle.


DC12-120(12V120Ah)




Discharge Characteristics Curve




Charge Characteristic Curve for Cycle Use(IU)




Cycle Life in Relation to Depth of Discharge




Relationship Between Charging Voltage and Temperature




Temperature Effects on Capacity




Storage Characteristics



Effect of Temperature on Long Term Life



Relationship of OCV And State of Charge(20°C)



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.

HENGYANG RITAR POWER CO.,LTD.
URL: www.ritarpower.com

Add: No.1 Huagong Road, Songmu Industrial Park, Shigu District, Hengyang, Hunan, China 421001
Tel: +86-734-8595528 Fax: +86-734-8595518 E-mail: sales@ritarpower.com

Version 19B-0