

DC12-75(12V75Ah)



Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	75Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 22.5 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 7.0 mΩ
Terminal	F5(M8)/F11 (M6)
Max. Discharge Current	750A (5 sec)
Design Life	12 years (floating charge)
Max. Charging Current	22.5 A
Reference Capacity	C3 57.3AH C5 64.6AH C10 71.4AH C20 75.0AH
Float Charging Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



DC (Deep Cycle) series batteries provide superior high integrity and reliability. It is specially designed for frequent cyclic charge and discharging. By using strong grids, thick plate and specially active material are designed for repeated deep-discharge applications. The DC series batteries offer 30% more cyclic life than the standby series. It is suitable for solar and wind renewable energy storage, mobility and medical equipment and cable TV etc.



ISO 9001



ISO 14001







OHSAS 18001



MH 28539



Dimensions



F11 TERMINAL

Length	260±2mm (10.2 inches)
Width	169±2mm (6.65 inches)
Height	211±2mm (8.31 inches)
Total Height	216±2mm (8.50 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A(25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	182.2	138.5	81.68	45.55	27.13	21.13	16.58	14.10	9.043	7.500	3.887
1.65V	167.7	129.5	77.37	44.00	26.22	20.48	16.08	13.66	8.972	7.429	3.866
1.70V	155.4	121.8	73.36	42.59	25.52	19.61	15.58	13.28	8.829	7.285	3.818
1.75V	142.6	114.0	70.46	41.25	24.54	19.11	15.16	12.92	8.687	7.214	3.750
1.80V	129.8	104.4	67.87	39.41	23.70	18.75	14.80	12.75	8.544	7.143	3.713
1.85V	101.5	86.39	57.54	35.18	21.68	17.46	13.88	11.74	8.047	6.714	3.679

Constant Power Discharge Characteristics : WPC(25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	310.1	241.5	148.4	85.52	51.29	40.13	31.95	26.69	17.63	14.71	7.760
1.65V	298.6	234.8	144.9	84.05	49.90	39.12	31.16	25.97	17.48	14.57	7.690
1.70V	278.7	222.2	138.0	81.58	48.66	37.62	30.18	25.31	17.27	14.29	7.622
1.75V	259.3	209.7	133.1	79.33	46.93	36.69	29.47	24.74	16.99	14.15	7.483
1.80V	239.0	193.9	128.8	76.09	45.86	36.49	28.90	24.40	16.71	14.00	7.414
1.85V	189.6	162.9	110.4	68.33	42.23	34.04	27.20	22.58	15.79	13.23	7.344


(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

The battery must be fully charged before the capacity test. The C₂₀ should reach 95% after the first cycle and 100% after the third cycle.


DC12-75(12V75Ah)




Discharge Characteristics Curve




Charge Characteristic Curve for Cycle Use(IU)




Cycle Life in Relation to Depth of Discharge




Relationship Between Charging Voltage and Temperature




Temperature Effects on Capacity




Storage Characteristics



Effect of Temperature on Long Term Life



Relationship of OCV And State of Charge(20°C)



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.

HENGYANG RITAR POWER CO.,LTD.
 URL: www.ritarpower.com

Add: No.1 Huagong Road, Songmu Industrial Park, Shigu District, Hengyang, Hunan, China 421001
 Tel: +86-734-8595528 Fax: +86-734-8595518 E-mail: sales@ritarpower.com

Version 21A-1-B