

TECHNICAL DATA SHEET
Ref. 530000
UNIPOLAR ELECTROMAGNETIC
BATTERY MASTER SWITCH
12VDC / 300A



GENERAL CHARACTERISTICS

Protection degree: IP65
 Ambient temperature: -40°C to +80°C
 Weight: 1.2 Kg approx.
 Contacts: Double cut copper
 Connections: not polarized
 Is working in all positions

FIELDS OF APPLICATION

Handling vehicles, industrial vehicles,
 agriculture machinery, industry...

CONTROL CIRCUIT

Breakaway starting current: 7 A (20 ms)
 Holding current: 0,3 A
 Absorbed power from the coil: 6 W
 Guaranteed interlocking tension: 9 V
 Disengaging tension: ≤ 4 V
 Connections by M5 terminals
 Tightening torque: 0.4 +/- 0.2 daN·m

POWER CIRCUIT

Connection: M10 terminals
 Tightening torque: 1.4 +/- 0.2 daN·m
 Type: normally open unipolar
 Max. using tension: 48 V
 Capacity:
 300 A in continuous
 2400 A during 1 seconds
 600A during 20 seconds

PARTICULAR CHARACTERISTICS:

Black galvanised finishing.
 Corrosion test: 200 h salt spray resistance



**ELECTRO
 MECANICA
 CORMAR**
 P.I. LLINARS PARK, C/ TECNOLOGIA, 82, NAVE N°7
 08450 LLINARS DEL VALLÈS
 BARCELONA (SPAIN)
 TEL. : + 34.93.732.35.91 - FAX : + 34.93.732.35.90
WWW.CORMAR.ES - info@cormar.es

Size diagrams

